

Examples of R-code

Example: Covariance calculation by numerical double integral.

```
[-----]
#First, install the package "cubature" with install.packages("cubature").
#You only need to do it once.

library(cubature) # load the package "cubature"
f <- function(x) { 6 * x[1] * (x[2] > x[1])} # This is the density, "x" is a 2D-vector

E.XY <- adaptIntegrate(function(x) x[1]*x[2]*f(x), lowerLimit = c(0, 0),
                       upperLimit = c(1, 1))
E.X <- adaptIntegrate(function(x) x[1]*f(x), lowerLimit = c(0, 0),
                      upperLimit = c(1, 1))
E.Y <- adaptIntegrate(function(x) x[2]*f(x), lowerLimit = c(0, 0),
                      upperLimit = c(1, 1))

cov.XY <- E.XY$integral - E.X$integral * E.Y$integral #E.X, E.Y, E.XY have several fields like
                                                       #E.X$integral E.X$error and so on.
                                                       #We need only the integral field.
cov.XY
[-----]
```

From:

<https://www2.math.binghamton.edu/> - **Department of Mathematics and Statistics, Binghamton University**



Permanent link:

https://www2.math.binghamton.edu/p/people/kargin/math447/r_example2

Last update: **2016/04/12 01:33**